

Rheem Water Heating Upgrade Chart | Residential Gas Models

Prestige® Series Condensing Tankless 12-Year Warranty



- Up to .93 UEF
- ENERGY STAR® Rated
- Continuous Hot Water
- Indoor/Outdoor Models Available
- 1/2" Gas Line Compatible
- 2" or 3" PVC Venting. Up to 60 ft. for 2" and 150 ft. for 3" Max
- Concentric Vent Kit Available
- Vertical or Horizontal Vent
- Freeze protection to -30F
- Built in Condensate Neutralizer
- EcoNet® Enabled – connect to EcoNet mobile app via EcoNet WiFi accessory kit, sold separately



MODEL NO.	MAX. GPM	EST. YEARLY ENERGY COST
RTGH-95DVLN-2	9.5	\$198
RTGH-90DVLN-2	9.0	\$198
RTGH-84DVLN-2	8.4	\$198
RTGH-68DVLN-2	6.6	\$198

Prestige® Series Powered Damper 12-Year Warranty



- .68 to .70 UEF
- ENERGY STAR® Rated
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- 3" or 4" Cat I, Double Wall or B-Vent
- 110V Power Damper with 19 ft. Power Cord
- Self Diagnostic Electronic Gas Valve
- EcoNet™ WiFi Kit Included which Operates on Apple and Android Devices
- Multiple Operation Modes with EcoNet® for Varying Usage
- Water Sensor with Audible Alarm will Alert EcoNet® Enabled Phone or Device



MODEL NO.	FIRST HOUR DEL.	EST. YEARLY ENERGY COST
PROP G38-40N RH69 PD	85 Gals.	\$264
PROP G50-40N RH67 PD	78 Gals.	\$271

Prestige® Series High-Eff. Condensing 6-Year Warranty



- .80 - .83 UEF
- ENERGY STAR® Rated
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- 2" or 3" PVC, ABS or CPVC Vent Lengths up to 60 ft. Max
- Concentric Vent Kit Available
- Vertical or Horizontal Vent
- 110V Power Damper with Power Cord
- Self Diagnostic Electronic Gas

MODEL NO.	FIRST HOUR DEL.	EST. YEARLY ENERGY COST
RHE40S	87 Gals.	\$222
RHE50	87 Gals.	\$231

Classic Plus® Series XR90 Induced Draft 8-Year Warranty



- .71 UEF
- ENERGY STAR® Rated
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- 29-Gallon Tank Capacity
- 60,000 BTU/h input
- 17-3/4" Diameter
- 110V Power Damper, 4.5 amps with 8 ft. Power Cord
- 3" or 4" Cat I, Double Wall or B-Vent
- Self Diagnostic Electronic Gas Valve

MODEL NO.	FIRST HOUR DEL.	EST. YEARLY ENERGY COST
PRO+G29-60N RH70 ID	93 Gals.	\$260

Classic Plus® Series Atmospheric 8-Year Warranty



- .58 to .66 UEF
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- Standard Replacement Parts

Classic® Series Atmospheric 6-Year Warranty



- .58 to .66 UEF
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- Standard Replacement Parts

ProtectionPlus® is a 4-year warranty extension kit that can be added to Classic® and Classic Plus® Series

ProtectionPlus® Part Number: SP20866

6	Year Limited Tank Warranty Becomes	10
8	Year Limited Tank Warranty Becomes	12



MODEL NO.	FIRST HOUR DEL.	EST. YEARLY ENERGY COST
PRO+G40-40N RH62	84 Gals.	\$280
PRO+G50-40N RH62	76 Gals.	\$284
PRO+G55-50N RH59	91 Gals.	\$298

MODEL NO.	FIRST HOUR DEL.	EST. YEARLY ENERGY COST
PROG29-32N RH63	63 Gals.	\$201
PROG40-38N RH62	64 Gals.	\$208
PROG50-38N RH60	85 Gals.	\$288



The new degree of comfort.®

July 2018

PRINTED IN U.S.A. 07/18 WP FORM NO. RH-301 Rev. 4

Rheem Water Heating Upgrade Chart | Residential Electric Models

Prestige® Series Hybrid 10-Year Warranty



- High 3.55 - 3.70 UEF
- ENERGY STAR® Rated
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- Dual 5000 Watt Stainless Steel Elements
- Dry Fire Protection
- 37-145°F Ambient Temp. Range is the widest in class
- LCD Touchscreen w/ Digital T-Stat w/ Multiple Modes of Operation
- Ability to access the unit and receive alerts remotely using the optional Econet® WiFi adapter, sold separately
- Water Sensor with Audible Alarm will Alert Econet® Enabled Phone or Device



MODEL NO.	FIRST HOUR DELIVERY	EST. YEARLY ENERGY COST
PROPH50 T2 RH350 DCB	67 Gals.	\$110
PROPH65 T2 RH350 DCB	75 Gals.	\$161
PROPH80 T2 RH350 DCB	89 Gals.	\$161

EcoNet™ makes it easier than ever for homeowners to save energy and achieve that perfect temperature – all while giving you the diagnostics you need to deliver that perfect level of service.

Prestige® Series 12-Year Warranty



- .93 UEF
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- Dual 5500 Watt Stainless Steel Elements
- LCD Screen with Digital T-Stat with Multiple Modes of Operation
- EcoNet® WiFi Kit Included, which Operates on Apple and Android Devices
- Audible Alarm and Water Sensor will Alert Econet® Enabled Phone or Device



MODEL NO.	FIRST HOUR DELIVERY	EST. YEARLY ENERGY COST
PROPE40 T2 RH95 EC2	56 Gals.	\$419
PROPE50 T2 RH95 EC2	63 Gals.	\$419

Marathon® Series Limited Lifetime Warranty



- .90 - .92 UEF
- Polyethylene Jacketed
- Polybutene Inner Tank
- Lightweight Unit
- 2-1/2" High Density Foam Insulated
- 240V/4500W Elements
- Titanium Lower Element
- Available in Larger "Pre-NAECA III" Capacities
- Recessed Brass Drain Valve
- Must be Registered by Homeowner on Date of Install for Applicable Limited Lifetime Warranty

MODEL NO.	FIRST HOUR DELIVERY	EST. YEARLY ENERGY COST
MR40245C	51 Gals.	\$424
MR50245C	59 Gals.	\$428

Classic Plus® Series 8-Year Warranty



- .90 - .93 UEF
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- Dual Stainless Steel Elements
- System Sentinel LCD Diagnostic Panel

Classic® Series 6-Year Warranty



- .92 - .93 UEF
- EverKleen® Self Cleaning
- Premium Grade Anode Rod
- Enhanced Flow Brass Drain Valve
- Stainless Steel Lower Element

ProtectionPlus® is a 4-year warranty extension kit that can be added to Classic® and Classic Plus® Series

ProtectionPlus® Part Number: SP20866

6	Year Limited Tank Warranty Becomes	10
8	Year Limited Tank Warranty Becomes	12



MODEL NO.	FIRST HOUR DELIVERY	EST. YEARLY ENERGY COST
PRO+E30 T2 RH95 EC1	46 Gals.	\$293
PRO+E40 T2 RH95 EC1	55 Gals.	\$419
PRO+E50 T2 RH95 EC1	63 Gals.	\$419
PRO+E55 T2 RH94 EC1	72 Gals.	\$424

MODEL NO.	FIRST HOUR DELIVERY	EST. YEARLY ENERGY COST
PROE30 T2 RH95	46 Gals.	\$293
PROE40 T2 RH95	55 Gals.	\$419
PROE50 T2 RH95	63 Gals.	\$419
PROE55 T2 RH94	72 Gals.	\$424



The new degree of comfort.®

July 2018

PRINTED IN U.S.A. 07/18 WP FORM NO. RH-301 Rev. 4

Rheem Water Heating Upgrade Chart | Residential Tankless Gas Models

Prestige® Series Condensing with Built-in Recirculation Tankless Gas 12-Year Warranty



- .94 UEF
- Vent with PVC up to 100' (3") and 50' (2")
- Instant Hot water at the tap
- Built-in Recirculation Pump reduces water waste
- 1/2" Gas line compatibility up to 24 ft.
- High-altitude capability – up to 10,000 ft. elevation above sea level
- Common Vent Two Units – Fewer wall penetrations, easier to install and more flexible option
- Compatible with Room Air Intake – More install options and faster to install (single units only, not common vented)
- Max GPM of 11 (on 199K BTU models)
- Auto-Learn Programming keeps up with your needs
- Low Flow Activation – Minimum flow and minimum activation flow rate of .50 GPM
- Low Emissions – Ultra low NOx burner meets SCAQMD rule 1146.2 requirements
- Timer-based recirculation pump with option for on-demand accessory wall switch
- Flame Sensor, Overheat Cut Off Limit Switch, Gas Leak Detector Sensor, Water Leak Detector Sensor Exhaust Temperature Sensor, Water Temperature Sensor

MODEL NO.	TYPE	MAX. GPM	EST. YEARLY ENERGY COST
RTGH-RH11DVLN	Indoor Direct Vent with Built-in Recirculation	11.0	\$196
RTGH-RH10DVLN	Indoor Direct Vent with Built-in Recirculation	9.9	\$196

Prestige® Series Condensing Tankless Gas 12-Year Warranty



- Up to .93 UEF
- Indoor/Outdoor Models Available
- WiFi Enabled – can connect to EcoNet® Mobile App via Tankless EcoNet Accessory Kit (REWRA630TWH)
- 1/2" Gas Line Compatible up to 24 ft.
- Recirculation Pump Kit Ready
- Built in Condensate Neutralizer
- Minimum Flow Rate of .26 GPM and Minimum Activation Flow Rate of .40 GPM Ensures Hot Water Even in Low Demand Situations
- 2" or 3" PVC Venting. Up to 60 ft. for 2" and 150 ft. for 3" Max
- Concentric Vent Kit Available
- Vertical or Horizontal Vent
- Freeze Protection to -30°F
- Digital Remote Control and 10 ft. of Thermostat Wire Included – Shows Temperature Setting and Service Code



MODEL NO.	TYPE	MAX. GPM	EST. YEARLY ENERGY COST
RTGH-95DVLN-2	Indoor Direct Vent	9.5	\$198
RTGH-95DVELN-2	Indoor DV (EcoNet® Included)	9.5	\$198
RTGH-95XLN-2	Outdoor	9.5	\$198
RTGH-95XELN-2	Outdoor (EcoNet included)	9.5	\$198
RTGH-90DVLN-2	Indoor Direct Vent	9.0	\$198
RTGH-90XLN-2	Outdoor	9.0	\$198
RTGH-84DVLN-2	Indoor Direct Vent	8.4	\$198
RTGH-84XLN-2	Outdoor	8.4	\$198
RTGH-68DVLN-2	Indoor Direct Vent	6.6	\$198
RTGH-68XLN-2	Outdoor	6.6	\$198

Mid-Efficiency Series Tankless Gas 12-Year Warranty



- .81 - .82 UEF
- Indoor/Outdoor Models Available
- WiFi Enabled – can connect to EcoNet® Mobile App via Tankless EcoNet Accessory Kit (REWRA630TWH)
- 1/2" Gas Line Compatible up to 24 ft.
- Recirculation Pump Kit Ready
- Minimum Flow Rate of .26 GPM and Minimum Activation Flow Rate of .40 GPM Ensures Hot Water Even in Low Demand Situations
- 3"/5" Concentric Vent System with Condensate Collector
- Fits Metal Fab. Inc., 3"/5" Concentric Venting Without an Adapter
- Vertical or Horizontal Vent
- Freeze Protection to -30°F
- Digital Remote Control and 10 ft. of Thermostat Wire Included – Shows Temperature Setting and ServiceCode



MODEL NO.	TYPE	MAX. GPM	EST. YEARLY ENERGY COST
RTG-RC95DVLN-1	Indoor Direct Vent w/ Recirc Pump	9.5	\$208
RTG-95DVLN-1	Indoor Direct Vent	9.5	\$208
RTG-95DVELN-1	Indoor DV (EcoNet® Included)	9.5	\$208
RTG-95XLN-1	Outdoor	9.5	\$228
RTG-95XELN-1	Outdoor (EcoNet included)	9.5	\$228
RTG-84DVLN-1	Indoor Direct Vent	8.4	\$208
RTG-84XLN-1	Outdoor	8.4	\$228
RTG-70DVLN-1	Indoor Direct Vent	7.0	\$137
RTG-70XLN-1	Outdoor	7.0	\$149

Parts and Accessories for Any Tankless Water Heater



Service Valves
Webstone Brand Tankless Service Valves
• **RTG20220AB** - Clean Brass for Low Lead Code
Includes cold and hot water set and pressure relief valve



Flush Kit
Connects to the service valves for an easy way to flush and de-scale your tankless water heater.
• **RTG20214**
Includes pump, hoses and 5-gallon bucket



AllClear™ Water Treatment System
Combat hard water and scale build up
• **RTG20251** - AllClear™ Water Treatment System
• **RTG20252** - Replacement Cartridge



EcoNet® WiFi Accessory Kit
Connect to EcoNet mobile app via Tankless EcoNet Accessory Kit
• **REWRA630TWH**



The new degree of comfort.®

April 2018

PRINTED IN U.S.A. 05/18 WP FORM NO. RHTK-301 Rev. 2

Rheem Water Heating Upgrade Chart | Commercial Tankless Gas Models and Systems

Commercial Tankless Models



RTGH-C95DVL

RTGH-C95XL

Commercial Tankless Models with Manifold Control



RTGH-CM95DVL

RTGH-CM95XL

Rheem Commercial Condensing Tankless Gas 5-Year Warranty

- 96% Thermal Efficiency
- Up to 185°F Max. Temperature Built-in
- Manifold Control Built-in Commercial Tankless Models Feature a Factory Installed Controller, Allowing up to 20 Units to be Connected in a Daisy-Chain, Side-by-Side Configuration – via an Included Manifold Control Cable
- Common Vent up to Ten Units with the Rheem Header Kits
- Service Valves Included with All Commercial Tankless Models
- Service Notifications – Alerts when Service is Needed
- Hot Start Programming Keeps the Commercial Tankless Unit in Ready-Fire position for Five Minutes After Use, Reducing the Cold Water Sandwich Effect in Back-to-Back usage
- Overheat Film Wrap – Detects if the Heat Exchanger Overheats and Shuts the System Down to Prevent Damage
- PPs Venting – Polypropylene Venting Options

MODEL NO.	TYPE	MAX. GPM
Commercial Tankless		
RTGH-C95DVLN	Indoor Direct Vent	9.5
RTGH-C95XLN	Outdoor	9.5
Manifold Ready Commercial Tankless		
RTGH-CM95DVLN	Indoor Direct Vent	9.5
RTGH-CM95XLN	Outdoor	9.5

New EZ-Rack™ Kit

- Mounts Easily to a Wall or Free Standing
- One Rack can Mount 2 Units in a Back-to-Back Free Standing Configuration
- Expands with Additional Kits to Hold any Number of Units
- Assembles Easily on the Jobsite in under 10 Minutes
- Indoor / Outdoor Use

Rheem Commercial Tankless Systems | 5-Year Warranty

This custom-built tankless solution arrives on the jobsite factory-assembled with single point connections including:

- RTGH-CM95 Units
- Factory installed system control manifold
- Pre-sized water & gas manifold
- Electrical wiring
- Condensate lines

Configurations










- Wall mounted system
- Wall hung system
- Free-standing system

System Options

- 2-6 tankless units per system

Engineered Solution

- Scalable from 11,000 BTU/h to 1,199,400 BTU/h per system (6 units max per system rack)
- Multiple configurations
- Options for future expansion

MODEL NUMBER	NUMBER OF UNITS	SYSTEM DESCRIPTION	FUEL TYPE	LAYOUT
WALL HANGING TANKLESS SYSTEM				
RTR-WH220DVLN	2-Units	Indoor Wall Hanging	Nat. Gas*	
RTR-WH220XLN	2-Units	Outdoor Wall Hanging	Nat. Gas*	
RTR-WH330DVLN	3-Units	Indoor Wall Hanging	Nat. Gas*	
RTR-WH330XLN	3-Units	Outdoor Wall Hanging	Nat. Gas*	
WALL MOUNT TANKLESS SYSTEM				
RTR-WM220DVLN	2-Units	Indoor Wall Mount	Nat. Gas*	
RTR-WM220XLN	2-Units	Outdoor Wall Mount	Nat. Gas*	
RTR-WM330DVLN	3-Units	Indoor Wall Mount	Nat. Gas*	
RTR-WM330XLN	3-Units	Outdoor Wall Mount	Nat. Gas*	
FREESTANDING TANKLESS RACK SYSTEM				
RTR-FS411DVLN	2-Units	Indoor Free Standing	Nat. Gas	
RTR-FS411XLN	2-Units	Outdoor Free Standing	Nat. Gas*	
RTR-FS420DVLN	2-Units	Indoor Free Standing	Nat. Gas	
RTR-FS420XLN	2-Units	Outdoor Free Standing	Nat. Gas*	
RTR-FS630DVLN	3-Units	Indoor Free Standing	Nat. Gas	
RTR-FS630XLN	3-Units	Outdoor Free Standing	Nat. Gas*	
RTR-FS421DVLN	3-Units	Indoor Free Standing	Nat. Gas	
RTR-FS421XLN	3-Units	Outdoor Free Standing	Nat. Gas*	
RTR-FS422DVLN	4-Units	Indoor Free Standing	Nat. Gas	
RTR-FS422XLN	4-Units	Outdoor Free Standing	Nat. Gas*	
RTR-FS632DVLN	5-Units	Indoor Free Standing	Nat. Gas	
RTR-FS632XLN	5-Units	Outdoor Free Standing	Nat. Gas*	
RTR-FS633DVLN	6-Units	Indoor Free Standing	Nat. Gas	
RTR-FS633XLN	6-Units	Outdoor Free Standing	Nat. Gas*	

*These models offered in LP, switch N for P in model number.



The new degree of comfort.®

April 2018

PRINTED IN U.S.A. 05/18 WP FORM NO. RHTK-301 Rev. 2